

SAFETY DATA SHEET**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Product name	Aral HighTronic R 5W-30
Product code	466927-BE02
SDS #	466927
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ mixture	Automotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
----------------------------------	---

1.3 Details of the supplier of the safety data sheet

Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam Castrol Germany GmbH, Überseeallee 1, 20457 Hamburg +49 (0) 800 863 73 70 E-mail address MSDSadvice@bp.com
----------	--

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)
-------------------------------	---------------------------------------

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition	Mixture
Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]	Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
Precautionary statements	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazardous ingredients	Not applicable.

Supplemental label elements	Safety data sheet available on request.
--------------------------------	---

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
---	-----------------

Product name		Aral HighTronic R 5W-30		Product code		466927-BE02		Page: 1/14							
Version		18		Date of issue		11 December 2025		Format		Germany		Language		ENGLISH	
Date of previous issue		23 December 2024.								(Germany)					

SECTION 2: Hazards identification

Special packaging requirements

Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
Other hazards which do not result in classification	Defatting to the skin. USED ENGINE OILS Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition	Mixture
Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.	

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1]

See Section 16 for the full text of the H statements declared above.

Type
[1] Substance classified with a health or environmental hazard
Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Product name	Aral HighTronic R 5W-30	Product code	466927-BE02	Page:	2/14
Version	18	Date of issue	11 December 2025	Format	Germany
Date of previous issue	23 December 2024.			Language	ENGLISH
					(Germany)

SECTION 4: First aid measures

Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	See: Section 11. Toxicological Information - Potential acute health effects: Eye contact

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
--------------------	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

Not suitable

Prolonged exposure to elevated temperature.

Germany - Storage code

10

7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name

Exposure indices

No exposure indices known.

DNELs/DMELs

Not available.

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.
All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.
Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

SECTION 8: Exposure controls/personal protection

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.
The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.
Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.
If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.
It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

SECTION 8: Exposure controls/personal protection

Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Refer to standards:	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.																																								
Colour	Amber. [Light]																																								
Odour	☒ Unfragranced																																								
Odour threshold	Not available.																																								
Melting point/freezing point	Not available.																																								
Initial boiling point and boiling range	Not available.																																								
Flammability	Not available.																																								
Lower and upper explosion limit	Not available.																																								
Flash point	☒ Closed cup: 238°C (460.4°F) [Pensky-Martens ASTM D 93]																																								
Auto-ignition temperature	<table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>☒bis(nonylphenyl)amine</td><td>440</td><td>824</td><td>EU A.15</td></tr></table>	Ingredient name	°C	°F	Method	☒ bis(nonylphenyl)amine	440	824	EU A.15																																
Ingredient name	°C	°F	Method																																						
☒ bis(nonylphenyl)amine	440	824	EU A.15																																						
Decomposition temperature	Not available.																																								
pH	Not applicable.																																								
Kinematic viscosity	☒ Kinematic: 71.2 mm²/s (71.2 cSt) at 40°C Kinematic: 9.3 to 12.4 mm²/s (9.3 to 12.4 cSt) at 100°C																																								
Solubility	<table><tr><th>Media</th><th>Result</th></tr><tr><td>water</td><td>Not soluble</td></tr></table>	Media	Result	water	Not soluble																																				
Media	Result																																								
water	Not soluble																																								
Partition coefficient n-octanol/ water (log value)	Not applicable.																																								
Vapour pressure	<table><tr><th rowspan="2">Ingredient name</th><th colspan="2">Vapour Pressure at 20°C</th><th colspan="3">Vapour pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>☒Distillates (petroleum), hydrotreated heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr><tr><td>Distillates (petroleum), hydrotreated heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr><tr><td>bis(nonylphenyl)amine</td><td><0.01</td><td><0.0013</td><td>EU A.4</td><td>0.0019</td><td>0.00025</td><td>EU A.4</td></tr><tr><td>Distillates (petroleum),</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr></table>	Ingredient name	Vapour Pressure at 20°C		Vapour pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	☒ Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191				Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191				bis(nonylphenyl)amine	<0.01	<0.0013	EU A.4	0.0019	0.00025	EU A.4	Distillates (petroleum),	<0.07501	<0.01	ASTM D 5191			
Ingredient name	Vapour Pressure at 20°C		Vapour pressure at 50°C																																						
	mm Hg	kPa	Method	mm Hg	kPa	Method																																			
☒ Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191																																						
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191																																						
bis(nonylphenyl)amine	<0.01	<0.0013	EU A.4	0.0019	0.00025	EU A.4																																			
Distillates (petroleum),	<0.07501	<0.01	ASTM D 5191																																						

SECTION 9: Physical and chemical properties

	solvent-dewaxed heavy paraffinic				
Density and/or Relative density	<1000 kg/m³ (<1 g/cm³) at 15°C				
Relative vapour density	Not available.				
Particle characteristics					
Median particle size	Not applicable.				
9.2 Other information					
Evaporation rate	Not available.				
Explosive properties	Not available.				
Oxidising properties	Not available.				
Pour point	-45 °C				

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401 Rabbit - Dermal - LD50 >5000 mg/kg OECD 402 Rat - Inhalation - LC50 Dusts and mists >5 mg/l [4 hours] OECD 403
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401 Rat - Dermal - LD50 >2000 mg/kg OECD 402 Rat - Inhalation - LC50 Dusts and mists >5.53 mg/l [4 hours] OECD 403

Acute toxicity estimates

N/A

Skin corrosion/irritation

Product/ingredient name	Result
-------------------------	--------

Product name	Aral HighTronic R 5W-30	Product code	466927-BE02	Page:	7/14
Version	18	Date of issue	11 December 2025	Format	Germany
Date of previous issue	23 December 2024.			Language	ENGLISH
					(Germany)

SECTION 11: Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit - Skin - Mild irritant OECD 404 Rabbit - Skin - Non-irritant to skin.
Serious eye damage/eye irritation Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	
Result Rabbit - Eyes - Non-irritating to the eyes. OECD 405 Rabbit - Eyes - Non-irritating to the eyes. OECD 405	
Respiratory corrosion/irritation Not available.	
Respiratory or skin sensitization Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	
Result Guinea pig - skin OECD 406 Result: Not sensitising Guinea pig - skin OECD 406 Result: Not sensitising	
Germ cell mutagenicity Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	
Result In vitro - Bacteria Bacterial Reverse Mutation Test Result: Negative In vitro - Mammal - species unspecified In vitro Mammalian Chromosomal Aberration Test Result: Negative In vivo - Mammal - species unspecified Mammalian Erythrocyte Micronucleus Test Result: Negative In vitro - Mammal - species unspecified In vitro Mammalian Cell Gene Mutation Test Result: Negative In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] Result: Negative In vitro - Mammal - species unspecified OECD [In vitro Mammalian Chromosomal Aberration Test] Result: Negative	
Carcinogenicity Product/ingredient name	
Result	

Product name

 Aral HighTronic R 5W-30

Version

 18

Date of previous issue

 23 December 2024.

Date of issue

 11 December 2025

Product code

 466927-BE02

Format

 Germany (Germany)

Language

 ENGLISH

Page:

 8/14

SECTION 11: Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic	Mouse - Dermal - Unspecified OECD 451 Result: Negative
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Mouse - Dermal - Unspecified OECD 451 Result: Negative
Reproductive toxicity Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic Result Rat - Oral OECD 421 Maternal toxicity: Negative Fertility effects: Negative Developmental: Negative Rat - Oral OECD 421 Maternal toxicity: Negative Fertility effects: Negative Developmental: Negative	
Specific target organ toxicity (single exposure) Not available.	
Specific target organ toxicity (repeated exposure) Not available.	
Aspiration hazard Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic Result ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1	
Information on likely routes of exposure	Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.
Potential acute health effects Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. Ingestion No known significant effects or critical hazards. Skin contact Defatting to the skin. May cause skin dryness and irritation. Eye contact No known significant effects or critical hazards.	
Symptoms related to the physical, chemical and toxicological characteristics Inhalation No specific data. Ingestion No specific data. Skin contact Adverse symptoms may include the following: irritation dryness cracking Eye contact No specific data.	
Delayed and immediate effects as well as chronic effects from short and long-term exposure Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion Ingestion of large quantities may cause nausea and diarrhoea. Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.	
Potential chronic health effects Not available.	
Conclusion/Summary [Product] Not available.	

SECTION 11: Toxicological information

General	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Conclusion/Summary [Product]	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
------------------------------	---

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Acute - EL50 OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute - EL50 OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia

SECTION 12: Ecological information

10 mg/l [21 days]

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Not expected to be rapidly degradable.

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F 31% [28 days] - Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F 31% [28 days] - Not readily

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil

Soil/water partition coefficient

Not available.

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No

Mobility Spillages may penetrate the soil causing ground water contamination.

Conclusion/Summary The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Distillates (petroleum), hydrotreated heavy paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No

Conclusion/Summary The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Conclusion/Summary [Product] This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

[Product](#)

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste

Yes.

[European waste catalogue \(EWC\)](#)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

[Packaging](#)

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References

Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user

Not available.

14.7 Maritime transport in bulk according to IMO instruments

Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

SECTION 15: Regulatory information

Product/ingredient name	%	Designation [Usage]
☒ Toluene	<0.01	48
☐ methanol	<0.0001	69

Labelling Not applicable.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are active or exempted.

Australia inventory (AIC) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (CSCL) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) ☒ At least one component is not listed.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Explosive precursors Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water 1 (classified according AwSV)

Prohibited Chemicals Regulation (ChemVerbotsV) When placed on the market in Germany, this product is not subject to the Prohibited Chemicals Regulation (ChemVerbotsV).

Occupational restrictions Observe employment restrictions in the following:
Gesetz zum Schutz der arbeitenden Jugend (Jugendarbeitsschutzgesetz – JArbSchG)
Gesetz zum Schutz von Müttern bei der Arbeit, in der Ausbildung und im Studium (Mutterschutzgesetz – MuSchG)

15.2 Chemical safety assessment A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

Product name	Aral HighTronic R 5W-30	Product code	466927-BE02	Page:	13/14
Version	18	Date of issue	11 December 2025	Format	Germany
Date of previous issue	23 December 2024.			Language	ENGLISH
					(Germany)

SECTION 16: Other information

EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SADT = Self-Accelerating Decomposition Temperature
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	
Full text of abbreviated H statements	H304 May be fatal if swallowed and enters airways.
Full text of classifications [CLP/GHS]	Asp. Tox. 1 ASPIRATION HAZARD - Category 1
History	
Date of issue/ Date of revision	11/12/2025.
Date of previous issue	23/12/2024.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.